

PRODUCT DATASHEET

SST PLUS CLAS A 75 7.5 W/4000 K E27

LED SUPERISTAR PLUS CLASSIC A FILAMENT | Dimmable LED lamps, classic bulb shape



Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to a halogen lamp
- Natural light spectrum with outstanding color rendering of CRI>90
- Greatly reduced blue component
- Improved visual comfort and reduced eye strain
- Very low energy consumption
- Instant 100 % light, no warm-up time
- Low flickering

Product features

- LED lamps for line voltage
- Beam angle: up to 300°



- Dimmable
- Color rendering index $R_a \geq 90$


TECHNICAL DATA

Electrical data

| | |
|--|-------------|
| Nominal wattage | 7.5 W |
| Construction wattage | 7.50 W |
| Nominal voltage | 220...240 V |
| Claimed equiv. conventional lamp power | 75 W |
| Nominal current | 38 mA |
| Type of current | AC |
| Inrush current | 1.46 A |
| Operating frequency | 50...60 Hz |
| Mains frequency | 50...60 Hz |
| Max. lamp no. on circuit break. 10 A (B) | 750 |
| Max. lamp no. on circuit break. 16 A (B) | 1200 |
| Power factor λ | > 0.50 |

Photometrical data

| | |
|---|---------------------|
| Luminous flux | 1055 lm |
| Nominal useful luminous flux 90° | 1055 lm |
| Luminous efficacy | 140 lm/W |
| Lumen main.fact.at end of nom.life time | 0.80 |
| Light color (designation) | Cool White |
| Color temperature | 4000 K |
| Color rendering index Ra | ≥90 |
| Light color | 940 |
| Standard deviation of color matching | ≤6 sdc _m |
| Rated LLMF at 6,000 h | 0.80 |
| Flickering metric (Pst LM) | 1.0 |
| Stroboscope effect metric (SVM) | 0.9 |



Light technical data

| | |
|------------------------------------|----------|
| Beam angle | 300 ° |
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |
| Rated beam angle (half peak value) | 300.00 ° |

Dimensions & Weight

| | |
|------------------|-----------|
| Overall length | 105.00 mm |
| Diameter | 60.00 mm |
| Maximum diameter | 60 mm |
| Product weight | 31.00 g |

Temperatures & operating conditions

| | |
|--------------------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
| Maximum temperature at tc test point | ≤65 °C |

Lifespan

| | |
|-------------------------------------|---------|
| Lifespan | 15000 h |
| Number of switching cycles | 100000 |
| Lumen maintenance at end of serv | 0.70 |
| Rated lamp survival factor at 6,000 | ≥ 0.90 |

Additional product data

| | |
|-----------------------------|---------|
| Base (standard designation) | E27 |
| Mercury content | 0.0 mg |
| Design / version | Frosted |

Capabilities

| | |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

Certificates & Standards

| | |
|--|-----------------|
| Energy efficiency class | D ¹⁾ |
| Energy consumption | 8.00 kWh/1000h |
| Type of protection | IP20 |
| Standards | CE |
| Photobiological safety group acc. to EN62778 | RG0 |

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

| | |
|-----------------|-----------------|
| Order reference | LSSPCLA75D 7,5W |
|-----------------|-----------------|

Energy labelling regulation data acc EU 2019/2015

| | |
|--|--------------|
| Lighting technology used | LED |
| Non-directional or directional | NDLS |
| Mains or non-mains | MLS |
| Light source cap-type (or other electric interface) | E27 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power | Yes |
| Length | 105.00 mm |
| Height | 60.00 mm |
| Width | 60.00 mm |
| Chromaticity coordinate x | 0.380 |
| Chromaticity coordinate y | 0.380 |
| R9 Colour rendering index | 0.00 |
| Beam angle correspondence | SPHERE_360 |
| Survival factor | 0.90 |
| Displacement factor | 0.50 |
| LED light source replaces a fluorescent light source | No |

| | |
|--------------|-----------------|
| EPREL ID | 642785 |
| Model number | AC33989,AC33989 |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075602632 | Folding box 1 | 60 mm x 60 mm x 145 mm | 46.00 g | 0.52 dm ³ |
| 4058075602649 | Shipping box 6 | 202 mm x 134 mm x 120 mm | 362.00 g | 3.25 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.